

# EVAP CART

Allows the EVAP smoke machine to be positioned close to the vehicle for service.



- Recessed area on top of the cart allows smoke machine to fit tightly and ensures its safety from tipping.
- Holding well for a standard sized SAE nitrogen tank of 60 or 75 cubic foot.
- Large shelf area for the adapter and other accessories that come with the smoke machine.
- Raised handle, large recessed rollers, and a minimum floor footprint for ease in moving the unit around the shop floor.

**No. 6626** – OTC No. 6525 LeakMaster, EVAP cart, and accessories.

**No. 6625** – EVAP cart only.

## OTC LeakMaster Specifications

Height	23 in. (58.4 cm)
Width	18 in. (45.7 cm)
Depth	9-1/2 in. (24.1 cm)
Weight	17 lb. (7.6 kg)
Ship Weight	20 lb. (9.0 kg)
Power Supply	12-volt DC
Amperage Usage	15 amps
Supply Pressure	13.0 in. H <sub>2</sub> O
Supply Volume	15 liters per minute
Operating Temp. Range	45° F to 140° F (7.2° C to 60° C)
Smoke Supply Line	12 feet (3.6 m)
Power Supply Line	12 feet (3.6 m)
Remote Starter Cable	12 feet (3.6 m)

## Accessories: (Included with No. 6626; also available separately)

<b>CEA-01</b>	3-1/2" Diameter Exhaust Cone (Qty. 2)
<b>CEA-02</b>	Assorted Cap Plug Kit
<b>CEA-03</b>	Smoke Diffuser Adapter
<b>HS-400AC</b>	400,000 CP Spotlight with 20 ft. Cord and Battery Clips
<b>CEA-04</b>	Standard SVC Port Adapter
<b>CEA-041</b>	25 ft. Nitrogen Coiled Hose
<b>CEA-042</b>	Small SVC Port Adapter
<b>CEA-049</b>	Double-ended Schrader Removal Tool
<b>SR00</b>	Water Trap Filter
<b>P-0716-UV</b>	Smoke Compound w/UltraTraceUV™ Technology



Manufactured by

**CHAMPION**  
ENGINEERING INC.

04-45, Printed in U.S.A

**SPX**

**OTC**

1-800-533-6127  
www.otctools.com

*Service Solutions, a unit of SPX Corporation*

655 Eisenhower Drive, Owatonna, MN 55060-0995  
Phone: 507-455-7000, International Sales: 507-455-7223