

2-Hole

Camshaft

Sprocket

18 mm

Hex Hd.

Camshaft

Sprocket

655 Eisenhower Drive Owatonna, MN 55060 USA Phone: (507) 455-7000 Tech. Serv.: (800) 533-6127 Fax: (800) 955-8329

Order Entry: (800) 533-6127 Fax: (800) 283-8665

International Sales: (507) 455-7290

Fax: (507) 455-7063

No. 511543

No. 511544

Operating Instructions for:

6476 (511543 & 511544)

Ford Camshaft Positioning Tool Set

Application: 1997 – 2002 4.6L Econoline, F-Series Truck (VIN W) 1997 – 2002 5.4L Econoline, Expedition, F-Series Truck


1997 - 2002 6.8 L V10 Econoline

1998 - 2002 5.4L Navigator

1. **Two-hole Camshaft Sprocket:** Use tool No. 511543 to position camshaft sprocket (2-hole) on the engine as shown.

18 mm Hex Hd. Camshaft Sprocket: Use tool No. 511543 with tool No. 511544 to position camshaft sprocket (18 mm hex hd.) on the engine as shown.

- Service the timing chain as required according to procedures in the vehicle service manual.
- 3. Torque fasteners to factory specifications.



NOTE:

- 511543 is the same as Ford No. 303-569 (T96T-6256-AR1) and 511544 is the same as Ford No. 303-570 (T96T-6256-AR2).
- This tool is used with No. 6477 (511545) Ford Camshaft Holding Tool.

WARNING: Wear eye protection that meets ANSI Z87.1 and OSHA standards.



© Bosch Automotive Service Solutions LLC July 25, 2014 Rev. C



2-Hole

18 mm

Hex Hd.

Camshaft

Sprocket

655 Eisenhower Drive Owatonna, MN 55060 USA Phone: (507) 455-7000 Tech. Serv.: (800) 533-6127

No. 511543

Fax: (800) 955-8329 Order Entry: (800) 533-6127 Fax: (800) 283-8665

International Sales: (507) 455-7290

Fax: (507) 455-7063

No. 511543

No. 511544

Form No. 107100

Operating Instructions for:

6476 (511543 & 511544)

Ford Camshaft Positioning Tool Set

Application: 1997 – 2002 4.6L Econoline, F-Series Truck (VIN W) 1997 – 2002 5.4L Econoline, Expedition, F-Series Truck

1997 – 2002 6.8L V10 Econoline

1998 - 2002 5.4L Navigator

 Two-hole Camshaft Sprocket: Use tool No. 511543 to position camshaft sprocket (2-hole) on the engine as shown.

18 mm Hex Hd. Camshaft Sprocket: Use tool No. 511543 with tool No. 511544 to position camshaft sprocket (18 mm hex hd.) on the engine as shown.

- Service the timing chain as required according to procedures in the vehicle service manual.
- 3. Torque fasteners to factory specifications.





511543


511544

NOTE:

- 511543 is the same as Ford No. 303-569 (T96T-6256-AR1) and 511544 is the same as Ford No. 303-570 (T96T-6256-AR2).
- This tool is used with No. 6477 (511545) Ford Camshaft Holding Tool.

WARNING: Wear eye protection that meets ANSI Z87.1 and OSHA standards.





© Bosch Automotive Service Solutions LLC July 25, 2014 Rev. C