



Best Forged Hammers[™] for tire service and industrial applications

GET SMASHED



Absorbs impact and vibration with indestructible handle

Outlast wood- and fiberglasshandle hammers by well over 30,000 overstrikes!







You break it (good luck!), we replace it, no question









Indestructable handle never needs replacement!

OTC B.F.H. SERIES

- Ergonomic rubber grip handle reinforced with steel bars resists breaking while absorbing impact and vibration.
- Drop-forged head is induction-hardened for long life, and contains steel locking plates that are specially bonded to ensure the head never becomes loose.
- ✓ Tire Service features for 5789ID-1032 and 5789ID-520.
 - Use top hook to tip a wheel; use sledge end hook to drag tire into position.
 - Bead breaking wedge has grooves and a convex shape to help drive tire lube into the bead.
- Meets ANSI / BS876 specifications for material, hardness and performance.

| OTC No. | Head Weight | Handle Length |
|--|-------------|---------------|
| Double Face Sledge Hammer, Indestructible Handle | | |
| 5790ID-624 | 6 lb. | 24" |
| 5790ID-630 | 6 lb. | 30" |
| 5790ID-824 | 8 lb. | 24" |
| 5790ID-830 | 8 lb. | 30" |
| 5790ID-1030 | 10 lb. | 30" |
| 5790ID-1230 | 12 lb. | 30" |
| 5790ID-1430 | 14 lb. | 30" |
| Club/Hand Drill Hammer, Indestructible Handle | | |
| 5791ID-312 | 2.5 lb. | 12" |
| 5791ID-412 | 4 lb. | 12" |
| 5791ID-416 | 4 lb. | 16" |
| Cross Peen Hammer, Indestructible Handle | | |
| 5792ID-216 | 2 lb. | 16" |
| 5792ID-316 | 3 lb. | 16" |
| Ball Pein Hammer, Indestructible Handle | | |
| 5793ID-2414 | 24 oz. | 14" |
| 5793ID-3214 | 32 oz. | 14" |
| Tire Service Hammer, Indestructible Handle | | |
| 5789ID-1032 | 10 lb. | 32" |
| 5789ID-520 | 5 lb. | 20" |







13-76 © 2013 Bosch Automotive Service Solutions. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials and specifications without notice. Certain kits may require additional cables or adapters. Product shipped may differ from photo(s) shown.

