



# **Bosch Tire Changer**

- ➤ Well suited to accommodate truck and bus wheels from 14" to 26" including tubeless rims or split rims
- ► Four clamping jaws with valved controlled clamping
- Movable control panel provides user added safety and flexibility
- ► Spring loaded mount/demount tool is for ease of operation
- ▶ Bi-directional chuck
- ► Single piece heavy steel frame

# **Models TCE 5210**

1694100216810	TCE 5210 3PH 230V / 3PH / 60Hz
1694100217810	TCE 5210 3PH 230V / 1PH / 60Hz



Inside clamping	14"-26"
Wheel width	31.5"
Tire diameter	64.5"
HP motor (Hydraulic)	2
Rotation Motor HP	2
Electrical requirements	220 V, 3Ph & 1ph available
Weight	1,310 lbs





# **Optional Accessories:**

### 1695400139810

Light Alloy Wheel Protection Adapters

#### 1695300102810

Tubeless roller





### **Bosch Heavy Duty Tire Changer**

- ► Capable of handling a large range of wheels from 14" to 56" including rims with wells, tubeless rims, or multipiece rims
- ► Bi-directional chuck with two rotational speeds
- ► Easily chuck, lift and operate in a vertical position
- ► Four clamping jaws with valved controlled clamping
- Movable control panel provides user added safety and flexibility

#### **Model TCE 5320**

1694100218810

TCE 5320 230V / 3PH

# **Specifications**

Inside clamping*	14"-56"
Wheel width	51"
Tire diameter	90.5"
HP motor (Hydraulic)	2
Rotation Motor HP	3-4
Electrical requirements	220 V, 3Ph
Weight	1,945 lbs

<sup>\*</sup>Large clamping range from 14" to 42" (extendable with special accessories up to 56")





# **Optional Accessories:**

1695301710810

Set of 56" Extensions Adapters

1695301711810

Light Alloy Wheel Protection Adapter

Scan here for more information on the TCE 5210HD or TCE 5320

