

## **GM SERVICE TOOLS**

ENGINE, TRANSMISSION, INTERIOR, AXLE, BRAKES, ELECTRICAL & BODY SERVICE

| V FIRE                               |   |  |   |
|--------------------------------------|---|--|---|
|                                      | TOOL  | APPLICATION  | USE   |
|                                      | Belt Tensioner<br>Compressor                  | 2.4L GM eAssist engines. 2012-<br>2016 LaCrosse, 2011-2014 Malibu,<br>2012-2017 Buick Regal.                       | Compresses the belt tensioner spring for easier engine drive belt replacement and starter generator servicing.  |
| 6725                                 | Mrs   |  | Similar to OE tool #EN-48932.   |
| 6750                                 | Diesel Fuel Hydrometer                        | Used for testing #1 and #2 grade diesel fuels.   | Test #1 and #2 grade diesel fuel composition and combustion characteristics. Helps diagnose fuel and drivability issues.  |
| Shades 1<br>For decore<br>Short WUSA | Injector Seal Installer<br>and Sizer Adapters | 1998-2014 GM engines with SIDI single seal injectors.  | Installs the Teflon seal onto the end of the injector to ensure proper injector installation. Includes seal installer/sizer and pilot cone.  Similar to OE tool #EN-48266.                            |
| 6757                                 | •   |  | 311111111 to GE 1001 #EN 40200.   |
|                                      | Evap Access Port Tool                         | All GM 5/16" EVAP line systems.  | Diagnose all GM 5/16" EVAP line systems. Use with the OTC 6522 LeakTamer for flow testing and leak testing.   |
| 6787                                 | •   |  | (Similar to OE tool #CH-48096)  |
| il:                                  | Oil Pressure and<br>Prelube Adapter           | 2005-Later GM Gen IV (4) and Gen V (5) engines, 4.8L, 5.3L, 6.0L, and 6.2L.  | Diagnose engine oil system issues. Adapter installs in place of the spin-on oil filter to connect pressure gauges to test oil system pressure.  |
| 7297                                 | NEW   |  | Can also be used to connect prelube equipment to the engine.  (Similar to OE tool #EN-47971)  |
|                                      | GM Duramax Injector<br>Puller                 | 2011-Later 6.6L Duramax Diesel, Isuzu.   | Assists in removing injectors from the cylinder head without damaging the injector body.  |
| 6777                                 | NEW   |  | (Similar to OE tool #EN-49774)  |
|                                      | Quick Connect Release<br>Tool                 | 2010-Later GM 2.8L and 6.6L diesel engines.  | Separates and prevents damage to the 4.8mm (3/16 inch) hydrocarbon injection quick-connector to service the fuel line bundle or replace fuel lines  |
| 6739                                 | NEW   |  | without removing unrelated components. (Similar to OE tool #CH-49736)   |
| 1 4                                  | Injector Seal Installer<br>and Sizer Adapters | 2010-Later GM 1.4L, 1.5L, 2.0L, 2.4L, 2.5L, 3.0L, 3.6L, 4.3L, 5.3L, and 6.2L engines.                              | Installs the dual seals onto the end of the injector to ensure proper injector installation. Includes two seal installation pilots for each groove, a seal installer driver, and a compression sizer. |
| 6756                                 | NEW   |  | Note: Some 2014-Later injectors have larger injector tips which require 6707 Injector Seal Installer Adapters.  |
| 0/30                                 |   |  | (Similar to OE tool #EN-49245)  |
|                                      | Crankshaft Rear Seal<br>Remover               | 2001-Later 6.6L Duramax diesel engine<br>found in GMT800, 2500HD, 3500, and<br>GMT900, GMC Sierra HD and Chevrolet | Special 3-jaw puller grabs the inner lip of the seal, preventing damage to the block and crank. Makes removing crankshaft rear seals easier and faster.   |
| 6740                                 | NEW   | Silverado HD. 2006-2016 Chevrolet<br>Express, GMC Savana   | (Similar to OE tool #J-44641)   |





|      | TOOL                                   | APPLICATION                     | USE  |
|------|--|---------------------------------|--|
| 6723 | Inner Pinion Bearing<br>Race Installer | 1998-2006 Suburban, Tahoe       | Installs inner pinion bearing race to desired position (Similar to J-45870 & J-8092)   |
| 6712 | Axle Seal Protector                    | 2011-Later                      | Protects axle seal from being cut or nicked, both of which can cause immediate or eventual leaks (Similar to J-44394-A)                                  |
| 5267 | Lift Pad Adapters                      | All                             | Used to properly lift the vehicle with a hoist (Similar to J-43625)  |
| 5089 | Air Brake Line Release<br>Tools        | 2003-Later Medium Duty trucks   | Separate connectors on the P/S system and EGR coolers without damage (Similar to J-45666 & J-42971)  |
| 6945 | Parasitic Draw Switch                  | All                             | Used with an amp meter to isolate parasitic amperage draws (Similar to J-38758)  |
| 6691 | Camshaft Retaining<br>Tool Set         | 2.8L/3.0L/3.6L                  | Lock the camshafts together at TDC to keep them from turning while setting timing (Similar to EN-48383)  |
| 6556 | Fuel Sender Lock Ring<br>Wrench        | 2003-2011 Cadillac CTS/SRX/STS  | Fits the newly designed 4 1/2" lock ring, which requires high torque to loosen and tighten (Similar to J-45747)  |
| 6706 | Injector Rail Assembly<br>Remover      | 2007-2014 GDI                   | Safely remove GDI fuel rails<br>(Similar to EN-49248)  |
| 6742 | Crankshaft Seal<br>Installer           | 2011-2013 Aveo/Cruze/Sonic/Volt | Safely installs front crankshaft seal<br>(Similar to KM-960)   |
| 6677 | Timing Chain Retainer                  | 2011-Later 2.0L/2.4L Ecotech    | Retain the timing chain and lower sprocket positions while servicing the upper sprockets, camshafts, valve springs, or valve seals (Similar to EN-48749) |
| 6759 | Flywheel Holding Tool                  | 2013-2014 2.0L & 2.5L           | Holds the flywheel in place for servicing the balancer or flywheel bolts (Similar to EN-50792)   |





|      | TOOL                                 | APPLICATION                            | USE   |
|------|--------------------------------------|--|---|
| 6758 | Front Crank Seal<br>Installer        | 2013-2014 2.0L & 2.5L                  | Allows for the installation of front crank seal without the removal of the cover (Similar to EN-50820 & EN48034)  |
| 6746 | Timing Chain Holding<br>Tool         | 2013-2014 2.0L & 2.5L                  | Retains the timing chain position relative to the crankshaft position (Similar to EN-50656)   |
| 6745 | Camshaft Actuator<br>Locking Tool    | 2013-2014 2.0L & 2.5L                  | Holds camshaft actuator in place to safely remove/install actuator bolt (Similar to EN-50793)   |
| 6744 | Tensioner Retaining Pin              | 2013-2014 2.0L & 2.5L                  | Relieves the tension on the timing chain tensioner for camshaft, actuator, and timing chain service (Similar to EN-50837)   |
| 6707 | Injector Seal Installer<br>Adapters  | 2013-Later 4.3L V6, 5.3L V8 or 6.2L V8 | Correctly install the injector seals for leak-free operation (Similar to EN-51105)  |
| 6708 | Injector Retaining Clip<br>Replacer  | 2013-Later 4.3L V6, 5.3L V8 or 6.2L V8 | Removes or installs the injector retaining clips without over-spreading to ensure proper retention of the injector to the rail (Similar to EN-51097)                            |
| 6710 | Fuel Pump Installation<br>Gauge      | 2013-Later 4.3L V6, 5.3L V8 or 6.2L V8 | Verifies that the camshaft fuel pump lobe is at<br>base circle position before installing the high<br>pressure fuel pump<br>(Similar to EN-51092)                               |
| 6788 | Pan Seal Cutter                      | All                                    | Pressed into the sealant and struck with a hammer in order to cut through the oil pan seals (Similar to J-37228)  |
| 6553 | Connecting Rod<br>Guides             | All                                    | Protects the crankshaft bearing surface from damage by nicking or scratching during piston and connecting rod removal or installation (w/ M8x1.0 threads) (Similar to EN-51454) |
| 2551 | Steering Column<br>Anti-Rotation Pin | 2005-Later                             | Installs into the steering column to keep the steering wheel orientation correct (Similar to J-42640)   |
| 6644 | Door Handle Spring<br>Retainer       | 2014-Later                             | Allows for door handle replacement without having to remove the interior door panel (Similar to BO-51363)   |
| 2550 | Key Fob Fixture                      | All                                    | Allows for quick and safe removal/installation of<br>GM flip key blades<br>(Similar to BO-51098)  |

|          |      | TOOL   | APPLICATION   | USE   |
|----------|------|--|---|---|
| <b>/</b> | 2549 | Cigarette Lighter<br>Socket Remover              | All   | Remove cigarette lighter socket without damage<br>to socket or dash<br>(Similar to J-42059)   |
|          | 6715 | Torque Converter<br>Seal Installer               | 1990-2011 FWD Automatic Transmission  | Installs torque converter seals without damage (Similar to J-28540-A)   |
| 27-      | 6713 | Seal Protector                                   | 2013-Later Chevrolet Trax, Buick Encore   | Protects transfer case Intermediate Drive Shaft (IDS) seal from splines of the IDS during shaft removal or installation (Similar to DT-50937)   |
|          | 6714 | Input Shaft Seal<br>Installer                    | 2013-Later Chevrolet Trax, Buick Encore   | Installs input shaft seal & side extension housing seals to proper depth (Similar to DT-50840 & J-8092)   |
|          | 6702 | Transmission Adapter Plate Bushing Replacer      | 2013-Later Chevrolet Trax, Buick Encore   | Replaces the mount bushing on the transmission adapter plate (Similar to DT-50839 & CH-50342)   |
|          | 6716 | Shift Rail Seal Installer                        | 2013-Later Manual Transmission<br>(Tremec TR 3160)  | Installs the shift seal on the Tremec TR 3160 transmission to the proper depth to ensure optimal seal life (Similar to DT-51077)  |
|          | 6743 | Pump Seal Installer Set                          | 2014-Later  | Protects, installs and sizes the torque converter<br>fluid seal ring into the stator support during unit<br>overhaul<br>(Similar to DT-51191)   |
| •        | 6724 | Trans Mainshaft<br>Bearing and Gear<br>Installer | 2014-Later Corvette (Manual)  | Prevent damage to components and are necessary as the transmission assembly (Similar to DT-51076 & DT-51076-10)   |
| 77.5     | 7040 | Trans Case Holding<br>Fixture                    | All   | Adjustable design for adapting to many different transmission case configurations as well as other components (Similar to J-36842)  |
|          | 6778 | GM Duramax<br>Injector Puller                    | 2001-2004 6.6L Duramax engines  | Designed to pull injectors<br>(Similar to J-44639)  |
|          | 6779 | GM Duramax<br>Injector Puller                    | 2005-2011 6.6L Duramax engines  | Designed to pull injectors<br>(Similar to J-46594)  |
|          | 6616 | GM Water Pump<br>Holding Tool                    | 2006-2014 2.0L I4 engines<br>2002- 2008 2.2L I4 engines with<br>engine code F<br>2004- 2008 2.4L I4 engines with<br>engine code B | Holds the timing chain in place for water pump replacement or removal. Unique design can be installed regardless of timing chain orientation. Keeps timing on GM engines when used properly during service.  (Similar to J-43651) |





