## **MUSCLE TOOLS Q3 2023 EDITION**

# HIGH TECH TO HARD TECH

BOSCH ROBINAIR OTC The most advanced diagnostics, tools & equipment





## **30-DAY MONEY BACK GUARANTEE**

Purchase and register a Bosch ADS 525X, ADS 625X, or 3824A ESI[truck] diagnostic tool. If you are not satisfied with your new tool, return it to Bosch within 30 days of invoice date for a full refund. For more information about the 30-Day Money Back Guarantee. call 1-855-BOSCHTECH (1-855-267-2483).

OTC TOOLS TO BEAT THE FLAT RATE



MONEY BACK

GUARANTEE



5950A Angled **Crimping Pliers** 











# Committed to quality because your reputation depends on it.

A complete lineup of connected diagnostic solutions that work together seamlessly to solve complex, cross-functional problems at every stage of the repair process. Engineered to optimize troubleshooting, boost efficiency, and alleviate tedious tasks while empowering you to focus your expertise on delivering quality repairs with precision and confidence.

Solutions for every job.

## boschdiagnostics.com

## **Unbeatable coverage for HD trucks,** construction equipment and more





#### Now with ELS\* (Extended License Subscription)

- All diagnostic functions continue after subscription expiration\*\*
- New coverage provided with active subscription
- Troubleshooting and Repair Software sold separately
- \* Effective on all contracts renewed or registered August 1, 2021 and thereafter
- \*\* Applies to Truck (3824A and 3824-08) and OHW (3824CBL-UPG and 3824-080HW) Coverage

## 3824A

#### ESI[truck] Heavy Duty Diagnostic Solution Truck, engine, and system coverage

- Truck brands: Freightliner, International, Kenworth, Mack, Volvo, Peterbilt, Sterling, Western Star, and more
- Engine brands: PACCAR, Perkins, Detroit Diesel-MBE, Mack, Navistar, Caterpillar, Deutz, MTU, and more
- System coverage: Transmissions, brake systems, trailer ABS, exhaust treatment, and more

## Expert-level diagnostics

- Automatic vehicle ID
- Fault code reading, reporting, clearing
- Diesel particulate filter (DPF) regeneration
- Cvlinder cut-out
- Injector coding and trim files
- Key component actuations
- Special tests
- Vehicle parameter modifications
- Includes 30-day free Troubleshooting & Repair Trial

## 3824A-TBL

## Heavy Duty Tablet Upgrade

- Everything you need to upgrade an existing 3824 ESI[truck] Tablet to the new and improved 3824A model
- Windows 10 Touchscreen tablet



## 3824-08R

## **Troubleshooting & Repair Subscription**

- Faster, more efficient heavy duty vehicle repairs
- 13,000+ procedures guide user through each step
- to troubleshoot vehicle issues
- Procedures by DTCs or by vehicle symptoms
- Technical Service Bulletins (TSBs) included

## 3824CBL-UPG

### ESI[truck] Off-Highway Upgrade Cable Kit with Introductory Software License

Add off-highway vehicle and machinery coverage for multiple manufacturers to your 3824 or 3824A ESI[truck] scan tool.

- Coverage included for: Construction equipment, agricultural vehicles, stationary engines, street sweepers and more
- Manufacturer coverage: Caterpillar, John Deere, Kubota, Perkins, Volvo, Massey Ferguson, SISU, Deutz, Deutz-Fahr, MTU, and more
- System coverage: Gearbox, HVAC, engine, steering, hydraulic systems, suspension, electronic modules, antipollution, central computer and more
- Diagnostic coverage: Manual processes, diagnosis info, measurable values, component actuations, ECU data, parameter IDs (PIDs), calibrations and resets, system technical data, wiring diagrams, vehicle technical data and vehicle maintenance info

## Kit contents:

- 10 cables for machinery, construction equipment, agricultural vehicles and more
- ESI[truck] off-highway software package with full diagnostic capabilities. Introductory off-highway software expires when your ESI[truck] heavy duty truck software expires
- Software renewals can be done simultaneously, ensuring continuous HD truck and off-highway vehicle coverage

## 3824BSC

## ESI[truck] Software and Adapter Kit

- Includes the ESI[truck] platform features, adapters, software, and coverage for use on your own Windows 10 device
- ESI[truck] diagnostic software with the functions and aftermarket coverage techs need, RP1210 Data link adapter, 6 and 9 pin cables, and HD/OBD II cables

## 3824-08

## ESI[truck] 1-Year Renewal License

• 1-Year (12-month) renewal license for existing ESI[truck] user

## 3824-08OHW

#### ESI[truck] Off-Highway 1-Year Software License

- 12-months of off-highway diagnostic coverage, including all coverage updates
- Used to renew initial software included with Off-highway upgrade cable kit with introductory software license

### For more information on software updates and off-highway coverage upgrades, visit boschdiagnostics.com

Off-highway cable upgrade kit and off-highway software only compatible with 3824A, 3824 and 3824BSC ESI[truck] diagnostic tools. Customer must first purchase Off-highway upgrade cable kit with introductory software (3824CBL-UPG) prior to purchasing or activating Off-highway 1-year software license (3824-080HW)







Month

12-



## MUSCLETOOLS Bosch Diagnostics

## **Battery and Electrical System Analyzers**



## **3920 VET 100 Circuit Analysis Tool** Quickly identify electrical issues in failed circuits

- Perfect tool for Data stream analysis using your scan tool
- Identify failed circuit component, wiring or PCM
- Simulates the sensor you are diagnosing by inputting a determined voltage at the sensor location
- Allows input voltage from .5VDC -7VDC in .5VDC increments
- Use your scan tool to verify if correct voltage is being applied to circuit
- Bypass sensor to send desired voltage back to PCM
- Works with 12V and 24V systems with vehicle voltage displayed. Also includes a "flashing" low battery voltage indicator



F00E9001013CM

## MMD 540H CAT III Multimeter

Auto-ranging digital multimeter for use in diagnostics of electronic circuits (automotive, fleet, motorcycle, marine or small engine)

### The MMD 540H offers:

- CAT III (1000v) safety rating for hybrid vehicle circuits
- Peak, Min/Max readings as fast as 1 millisecond
- Inductive RPM clamp for conventional and DIS ignition systems
- Fused diagnostic test leads provide safe troubleshooting (up to 20 amps) at the circuit fuse location
- K-Type thermocouple for quick temperature measurement
- Large LCD display with bright backlighting and auto shutdown
- Rugged nylon case with handle for storage



3926

## **BAT 35** Vehicle Computer Memory Saver

BAT 35 maintains the memory of the on-board vehicle computer to prevent losing memory settings when you disconnect a battery.

- Retain computer memory and on board memory sets such as: keyless entry codes, seat memory, digital radio settings, clocks, car alarms etc.
- Includes 12V, 7amp hour lead acid, sealed battery for long life expectancy
- Six LED indicator lights, three for charging functions and three for power storage conditions for ease of use
- Built-in OBD II cable for vehicle power supply while vehicle battery is disconnected



**BAT155** 

## **BAT 155** Heavy Duty Battery and Electrical System Analyzer

- 100 6,000 Cold Cranking Amp (CCA) Test Capacity
- Enables Testing Battery Packs (Multiple Batteries connected together) in the vehicle
- Infrared Temp Sensor for measuring battery temp (increases accuracy of CCA measurement)
- Optional Amp Probe and Voltmeter
- Tests 6V, 12V batteries and 12V, 24V charging systems



0684010050480

## FSA 050 CAT IV, CAT III Insulation Tester

Convenient, wireless testing for electric and hybrid drives (Cars, trucks, SUVs, etc). The FSA 050 CAT IV, CAT III Insulation Tester functions as a standalone multimeter or high-voltage meter. Alternatively, transmit the test data wirelessly to your Windows device for further review and analysis.

Future-proof as a standalone device or as a special accessory.

## Common use cases:

- High voltage electric AC compressor
- High voltage shorts to ground
- Battery Packs
- Determine Isolation or insulation faults

## TPA 300 TPMS Programming Tool




## Pair with any Bosch diagnostic tool to program new sensor IDs via OBD

- Activate and read TPMS sensor data, program sensors, check remote keyless entry signal and display sensor data in seconds
- Perform OBD II relearns within minutes when paired with a compatible Bosch manufactured diagnostic scan tool
- Full database of indirect, manual and auto relearn procedures
- Intuitive, full-color display with easy vehicle lookup by make, model and year
- Supports all known OE and aftermarket programmable sensors for all light vehicles
- New features, vehicles and sensor coverage added regularly
- Includes 3 years of free software updates

## **ADAS Recalibration System**

## **DAS 3000**

A complete ADAS recalibration package that enables shops to quickly, easily and precisely recalibrate Automated Driver Assist System



## **Calibration Mats**

Brand specific equipment for the proper calibration of the Rear and Surround View cameras according to the OEM specifications implemented by Bosch routines and workflows.

## **Near Range Camera Systems** for Volkswagen group





Calibration set for 360° Cameras Generation 2: CTA 500-1

**Near Range** Camera Systems for Mercedes-Benz





Calibration set for Rear Camera: **CTA 511-1** 

## Leak Testers

Safe and cost-effective leak detection solutions for light and heavy duty vehicles



**SMT 300** 

## **SMT 300** LeakTamer II EVAP & Diagnostic Smoke Machine

Multi-purpose tester designed not only for EVAP testing but for leak detection in any low pressure closed system including oil leaks, exhaust leaks, wind leaks, water leaks, EGR leaks and many more

- Fully featured machine with graduated smoke flow control valve, air flow meter, and pressure/vacuum decay gauge
- Full complement of accessories and storage case included



**SMT 500** 

## **SMT 500 Portable Leak Detector**

- On Board Air compressor eliminates need for shop air or inert gas tank during use
- Variable flow control detect leaks as small as 0.01" in sealed systems
- Pressure decay testing
- Compact, lightweight design (ultra-portable at 11 lbs)




**HPT 500** 

## **High Pressure Leak Tester**

- Produces leak detection "smoke" at higher pressure than standard machines (up to 20psi) for higher pressure systems
- Higher flow rate fills the system with smoke up to 5 times faster
- Ideal for finding leaks in exhaust after-treatment systems
- Test entire system, from intake to exhaust, in one 15 minute test
- High-pressure and large volume systems found in heavy-duty truck and turbocharged passenger vehicles



# Complete YF service



## What do I need to service R-1234yf systems?

- A new machine meeting SAE J2843 standard; Robinair's AC1234-4 or AC1234-9
- A new leak detector meeting SAE J2913 standard; Robinair's LD3, LD5 or LD7
- A syringe-type oil injector to inject oil back into the system; Robinair's 18465
- Optional tracer gas leak detector to reduce cost searching for leak; Robinair's LD9-TG

## **A New Leak Detector**

Your existing leak detector may not recognize R-1234yf, meaning you may not catch an expensive refrigerant leak. Invest in one that meets SAE J2913 and J2791 standards.

- LD3 leak detector automatic calibration and audible alerts
- > LD5 leak detector with bar graph mode and color display
- LD7 premium leak detector with bar and pinpoint graphing modes and detects both R134a and R1234yf.



## New Syringe-Type Oil Injectors

AC1234-4

1234yf systems have different fittings and couplers, requiring a new syringetype oil injector to put oil back into the system. Current SAE standards for 1234yf service does not allow automatic oil injection on a machine.

- > 18465 PAG-labeled 1234yf injector for low-voltage systems in gas and diesel vehicles
- > 18470 POE-labeled 1234yf injector for electric and hybrid vehicles



AC1234-9

Connected

18465 shown



800.533.6127



## Robinair A/C Tools & Equipment

## MUSCLETOOLS



## 80211TMP

### Bluetooth temp probes master kit

- Read and track temperatures from multiple locations from your A/C machine
- Use up to 2 probes per compatible Robinair machine
- Enables WiFi and Bluetooth capabilities on NI and AC1234-4 machines

## What wireless accessories fit my machine?

Non-wireless A/C Machine Wireless Enabled A/C Machine

| A/C Machine                             | VCI      | Temp Probes | VCI       | Temp Probes     |
|---|----------|-------------|-----------|-----------------|
| 34288NI, 34788NI,<br>34788NI-H, 34988NI | 80211VCI | 80211TMP    | ACS-250*  | 80213 or 80212* |
| 34998, AC1234-9                         | _        | _           | ACS-250** | 80213 or 80212  |
| AC1234-4                                | 80211VCI | 80211TMP    | ACS-250*  | 80213 or 80212* |



### 80211VCI

### VCI master kit + database

- Enables WiFi and Bluetooth capabilities on NI and AC1234-4 machines
- Wirelessly gather and transmit vehicle year, make and model info to your compatible Robinair machine
- Includes current-year refrigerant capacity database to quickly determine correct refrigerant charge, oil type and oil capacity
- Also reads generic OBDII codes to help troubleshoot A/C system issues

\*Use of ACS-250, 80212 or 80213 on NI or AC1234-4 requires machine first be WiFi/Bluetooth enabled using either 80211TMP or 80211VCI master kit \*\*Database purchase required for vehicle refrigerant capacity

## Find leaks and diagnose system issues faster

Connected accessories, leak detectors, refrigerant analyzers and tracer gas detectors for R-134a and R-1234yf service



#### 16995 R-ID Plus refrigerant identifier/analyzer

- Analyze R-134a and R-1234yf refrigerant for purity and contamination
- Prevent contaminated refrigerant from being pulled into your machine
- Includes printer to add refrigerant purity to service report
- R-134a and R-1234yf tank adapter; R-134a and R-1234yf hoses included
- Available as 16990 R-ID without printer



#### EVDC®100 A/C Electronic Variable Displacement Compressor Tester

- Eliminates misdiagnosing electronic variable displacement A/C
- compressors
- Quickly diagnosis and verify valve function, lowering total repair time and costs
- Adjustable tester output
- Includes connect adapters for both old and newer style compressors
- Heavy duty battery clips and cable provides power from vehicle battery, eliminating the need for batteries
- Made in the USA

#### LD7 Premium refrigerant leak detector

- Detects R-1234yf and R-134a leaks for use on most vehicles
- Sweep, bar graph and line graph modes make finding leaks faster, easier
- Features audible detection alert, UV LED lights for use with UV dye and inspection light
- Sensor life up to 10 years for reliable leak detection
- Available as LD3 and LD5 versions

## LD9-TGKIT

## Tracer gas leak detector service kit

- Use inexpensive Tracer gas instead of costly refrigerant to find leaks
- Tracer gas is a 95% nitrogen, 5% hydrogen mixture and harmless to A/C systems
- The LD9-TG detector sniffs out hydrogen, detecting leaks faster and at less cost
- Kit includes 1234yf coupler, 134a coupler, Tracer gas detector, hose and Tracer gas regulator
- Available as LD9-TG, Tracer gas detector only

## **Robinair A/C Tools & Equipment**

R-134a Systems

| <b>Combining Simple Operation</b> |  |
|-----------------------------------|--|
| with Superior Accuracy            |  |

These machines will test, recover and recharge

| R-134a and R-1234yf automotive A/C system quickly and accurately.   |                  | Į,                   |                      | Ķ,                                |  |                      |  |
|---|------------------|----------------------|----------------------|-----------------------------------|--|----------------------|--|
| Features  | 34288NI          | 34788NI              | 34788NI-H            | 34988NI                           | 34998  | AC1234-4             | AC1234-9                                     |
| Fully Automatic Function: Program to recover, vacuum,<br>leak test and charge without operating panel valves.   | Manual<br>Valves | ~                    | ~                    | ~                                 | 1  | ~                    | <i>√</i>                                     |
| Automatic fluid drain/inject  | Oil drain        | Oil drain/inject*    | Oil drain            | Oil drain/inject,<br>dye inject** | Oil drain/inject,<br>dye inject**            | Oil drain            | Oil drain                                    |
| A/C System Flush: Flushes a vehicle's A/C system with<br>refrigerant, eliminating any residual oil or other liquid.<br>(Flushing adapters not included)                         | -                | -                    | ~                    | 1                                 | ~  | J                    | 1  |
| Save & print before and after service data: Allows the user<br>to store before and after service information by vehicle<br>and print this information to provide to a customer. | -                | 1                    | 1                    | 1                                 | 1  | J                    | J  |
| Visual & Audible Alarm: Notifies the user when service is complete, or if a problem has occurred.   | -                | 1                    | 1                    | 1                                 | ~  | 1                    | 1  |
| Vacuum Leak Test: Monitors level after evacuation,<br>informs of possible leak.   | -                | ~                    | 1                    | 1                                 | 1  | 1                    | J  |
| Automatic Air Purge: Eliminates system-damaging air<br>without monitoring gauges or opening valves.   | 1                | ~                    | 1                    | ~                                 | 1  | 1                    | <i>√</i>                                     |
| Automatic Refrigerant Refill: Maintains a user-selectable<br>amount of refrigerant in an internal vessel and signals<br>when it's time to change supply tank.                   | -                | ~                    | 1                    | ~                                 | 1  | J                    | 1  |
| Vacuum Feature: Defaults to 15 mins, programmable up to<br>99 mins. "Remaining time" is displayed.  | 1                | 1                    | 1                    | 1                                 | ~  | 1                    | 1  |
| Multilingual display  | 4.3" color LCD   | 4.3" color LCD       | 4.3" color LCD       | 7" color LCD                      | 10.5" hi-res<br>touch screen                 | 4.3" color LCD       | 10.5" hi-res<br>touch screen                 |
| Refrigerant Charging:   | Low only         | High, low<br>or both | High, low<br>or both | High, low<br>or both              | High, low<br>or both                         | High, low<br>or both | High, low<br>or both                         |
| Refrigerant Management System: Displays refrigerant use<br>and monitors remaining filter life. Prompts appear when<br>1/3 of filter life remains.                               | 1                | ~                    | ~                    | 1                                 | 1  | J                    | J  |
| Electric Vehicle: Capable of servicing high voltage electric compressor A/C systems.  | -                | -                    | 1                    | -                                 | -  | 1                    | <i>√</i>                                     |
| Printer   | 30038            | 30038                | 30038                | Included                          | Mopria Print<br>Service wireless<br>printing | 30038                | Mopria Print<br>Service wireless<br>printing |
| Bluetooth temp probes: Dual-zone temp recording and reporting   | 80211TMP         | 80211TMP             | 80211TMP             | 80211TMP                          | 80212 or 80213                               | 80211TMP             | 80212 or 80213                               |
| Bluetooth VCI: Reads YMME and refrigerant capacity  | 80211VCI         | 80211VCI             | 80211VCI             | 80211VCI                          | ACS-250***                                   | 80211VCI             | ACS-250***                                   |


\* One oil bottle. \*\* Two oil bottles and one UV dye bottle. \*\*\* ACS-250 requires purchase of 34001 or 34002 database to read YMME and display refrigerant capacity

All machines use 34724 filter and 13172 maintenance kit

## Syringe-type Injectors

## Oil injectors for YF, EV and hybrid vehicles

Use these syringe-type injectors to add oil to a fully pressurized A/C system. Fill the barrel with the amount of oil needed, connect the injector, and press the plunger. Not recommended for UV dye injection.



18490 POE labeled for hybrid and electric vehicles

18465 PAG-labeled 1234yf injector for low-voltage systems in gas and diesel vehicles

## **Manifolds and Hose Set**



## 41234

## R1234yf Aluminum Manifolds and Hose Set

• Easy-to-read 3-1/8" adjustable gauges

• Durable aluminum manifold block with fittings



R-1234yf Systems

2-Way Brass Manifold R134a Manifold Hose Kit

• 90° manual couplers •72" R134a hose set

8



## NEW CONNECTED ADAPTER EXPANSION KITS



## CA6636-HCB HONDA CONTROL ARM BUSHING KIT

- Easier Honda and Acura control arm bushing removal & installation
- Unique adapter shapes and sizes fit most Honda and Acura vehicles from 2001 2015
- For use with CA7149 connected adapter starter kit, CA6630 connected adapter professional kit, or CA6636 connected adapter C-frame
- Control arm bushings found on Honda Accord, Civic, Element and CRV; Acura TSX, CSX, I\*LX and RSX



## CA6636-EXT CONNECTED ADAPTER EXTENSION

- Adds clearance and spacing for ball joint studs on the drive screw side
- Allows the C-frame to be oriented in either direction and in tight spaces
- For use with CA7149 connected adapter starter kit, CA6630 connected adapter professional kit, or CA6636 connected adapter C-frame



## CA7149 CONNECTED ADAPTER STARTER KIT

- 7 connected cups & adapters hold securely to C-frame and drive screw
- 235+ vehicle models covered, from Honda Accord to Ford F-350s
- Backwards compatible with all OTC ball joint kits and adapters



## CONNECTED ADAPTER PROFESSIONAL KIT

- 25 connected cups & adapters hold securely to C-frame, making R&I easier
- 600+ vehicle models covered, including compact cars up to HD trucks
- Fully illustrated manual with adapter callouts, diagrams and instructions by vehicle model
- Backwards compatible with all OTC ball joint kits and adapters



**QUESTIONS?** 

800 533 6127

## New Navistar Tools and Diesel Engine Adapters



## 5865

- EGR Valve Puller • Aids in removal of EGR valve on select Navistar engines
- $\bullet$  Works on 2010 MaxxForce 9, 10 & DT engines; 2013 N9 and N10 engines with SCR
- Similar to Navistar OE tool ZTSE4941



## 5867

### **Cab Mount Bushing Kit**

- Easier removal and installation of cab-mounting bushings on select Navistar bodies
- Extra-large C-frame provides clearance and necessary force to R&E cab-mounting bushings
- Works on the following bodies: 9000i Series, DuraStar, HV, HX, LoneStar, LT, MV, PayStar, ProStar, RH, TerraStar, TranStar, WorkStar
- Similar to Navistar OE tool ZTSE4928



## 1750A

## 6000 LB. Revolver Diesel Engine Stand

Navistar and Detroit Diesel adapters

- 96 to 1 ratio worm and gear set rotates components a full 360°; handle locks in any position.
- Includes 205061 universal mounting plate for use with individual engine adapter plates.

#### 1750

Engine stand without universal engine adapter assembly





1750-47366

Mack / Volvo

1750-4649

Navistar / IH



1750-47022 Detroit Diesel



1750-47389

Detroit Diesel

1750-4940 Navistar / IH



1750-4789 Navistar

| Item       | Description                                  | Application   | Brand                                    | Component | Requires use of<br>205061 plate |
|------------|--|---|--|-----------|---------------------------------|
| 1750-47389 | Detroit Diesel engine adapter plate          | DD13 & DD15 engines   | Detroit Diesel                           | Engine    | No                              |
| 1750-47366 | Mack / Volvo engine adapter plate            | MP7 / D11 engines   | Mack / Volvo                             | Engine    | No                              |
| 1750-4940  | Navistar / IH MaxxForce engine adapter plate | 2010 - 2016 Navistar MaxxForce DT,<br>MaxxForce 9, MaxxForce 10 engines   | Navistar /<br>International<br>Harvester | Engine    | Yes                             |
| 1750-4649  | Navistar / IH MaxxForce engine adapter plate | 2004 - 2009 International Harvester DT466,<br>DT570, HT570; Navistar MaxxForce DT,<br>MaxxForce 9, MaxxForce 10 engines | Navistar /<br>International<br>Harvester | Engine    | Yes                             |
| 1750-4789  | Navistar MaxxForce engine adapter plate      | 2007 - later MaxxForce 11, MaxxForce<br>13 engines  | Navistar                                 | Engine    | Yes                             |
| 1750-47022 | Detroit Diesel MBE 900 engine adapter plate  | Detroit Diesel 2004 - 2007 MBE 900 engines  | Detroit Diesel                           | Engine    | No                              |

## Safely lift and hold Class I, II and III vehicles - up to 3.5 tons



### LDJA2 2-ton aluminum racing jack

- Lift compact sedans to small crossovers
- Light, sturdy aircraft aluminum with carry handles is ideal for service trucks and portability

### SA02 2-ton aluminum jack stands

- Pin-style jack stand for fast, secure vehicle holding
- Aircraft aluminum construction for rust-free
  performance

### LDJA2-SET

• Includes LDJA2 2-ton aluminum jack and SA02 2-ton aluminum stands



### LDJ2 2-ton low profile service jack

• Long reach low-profile jack for low ground clearance vehicles

### LDJ35 3.5-ton steel service jack

- Safely handles large SUVs and crossovers to 3/4-ton pick-ups
- Rolled edges add strength to resist twisting for larger loads



## S03 3-ton steel jack stands S04 4-ton steel jack stands

- Ratcheting design cannot be released under load
- Formed and welded steel base with baked enamel finish for strength, corrosion resistance
- S03 and S04 sold as a pair







## **Service Jacks**

**Jack Stands** 

|                      |   |  | -   |
|----------------------|---|--|---|
|                      | LDJA2   | LDJ2   | LDJ35   |
| Capacity             | 2-ton   | 2-ton  | 3.5-ton   |
| Lifting range        | 3-1/4" (saddle removed) - 18-5/8"                 | 3"   | 5.2" to 21.9"   |
| Padded handle length | 47.6"   | 50"  | 50" spring-loaded padded lower handle                     |
| Footprint            | 11.875" x 25.125"                                 | 14.29" x 32.67"                                    | 14.5" x 28.5"   |
| Reach                | 72.75"  | 69"  | 78.5"   |
| Saddle               | 4-1/2" dia., round                                | 4" dia. round, rubberized                          | 6" dia., flat steel, rubberized, pinned to<br>lifting arm |
| Casters              | 4; 2.5" front fixed (2),<br>1.75" rear swivel (2) | 4; 2.75" front fixed (2),<br>2.75" rear swivel (2) | 4; 3.15" front fixed (2),<br>2.5" rear swivel (2)         |
| Frame height         | 6"  | 2.75"  | 6.25"   |
| Jack pack            | LDJA2-SET, includes SA02 jack stands, pair        | N/A  | N/A   |







#### SA02 (sold as a pair) S03 (sold as a pair) S04 (sold as a pair) 3-ton Capacity 2-ton 4-ton 15.44" Max height 17-11/16' 23-13/16' Min height 9-1/2" 12" 15-1/2" 7" round base 8-1/4" x 7-1/2" square base; welded foot pads Footprint Square base; welded foot pads Adjustment Pin lock; 6 slots Ratcheting; 11 teeth Ratcheting; 11 teeth Saddle Flat-top style, 2.17" x 2" V-notch style, 1" x 3.5" V-notch style, 1.3" x 4.3"

## MUSCLETOOLS OTC Service Jacks and Stands

## Covering the big classes for lifting it all



#### HDJ5P 5-ton hydraulic service jack with air-assist

• Same as HDJ5, with air/hydraulic assist to reduce effort to raise, lower vehicles

## HDJ10P 10-ton hydraulic service jack

## with air-assist

Same as HDJ10, with air/hydraulic assist to reduce effort to raise, lower vehicles



| 5, 10, 20-ton<br>heavy-duty jacks | HDJ5   | HDJ5P   | HDJ10   | HDJ10P  | HDJ20   |
|-----------------------------------|--|---|---|---|---|
| Capacity                          | 5-ton  | 5-ton air-assist                                      | 10-ton  | 10-ton air-assist                                     | 20-ton  |
| Lifting range                     | 6" to 22"  | 5-7/8" to 22"   | 6.3" to 22"   | 6-3/8" to 22"   | 7-1/2" to 23.8"                                   |
| Air pressure                      | -  | 80–120 PSI  | -   | 80-120 PSI  | -   |
| Handle<br>length                  | 43" 3-position<br>with lock and<br>release controls  | 45.4" 3-position<br>with lock and<br>release controls | 43-1/4" 3-position<br>with lock and<br>release controls | 45.4" 3-position<br>with lock and<br>release controls | 47-1/2", 3-position<br>spring-assisted<br>locking |
| Footprint                         | 15" x 56"  | 14.2" x 55.5"   | 18" x 60"   | 18.9" x 60.8"   | 18-1/8" x 61-3/8"                                 |
| Reach                             | 47"  | 87"   | 51"   | 90"   | 110.4"  |
| Saddle                            | 5-1/8" dia., round                                   | 5.1" dia., round                                      | 6" dia., round  | 5-3/4" dia., round                                    | 6-1/2" dia.,<br>steel crown                       |
| Casters                           | 4; 4.4" fixed front (2),<br>2.8" mid-body swivel (2) | 4; 4.4" fixed front (2),<br>2.8" mid-body swivel (2)  | 4; 5.6" fixed front (2),<br>3.6" mid-body swivel (2)    | 4; 5.6" fixed front (2),<br>3.6" mid-body swivel (2)  | 6; 4 front fixed;<br>2 mid-body swivel            |
| Frame height                      | 7.9"   | 7.5"  | 9.8"  | 9.8"  | 10.2"   |

## **OTC Service Jacks and Stands**

## MUSCLETOOLS



S06 6-ton steel jack stands

- Ratcheting design cannot be released under load
- Formed and welded steel base with baked enamel finish for strength, corrosion resistance



- S020 20-ton steel jack stand
- Large 15-1/2" square base safely holds up to 40,000 lbs
- Dual pin-style stand with four adjustment positions



#### S022 22-ton steel jack stands

- 11" flat square base prevents sinking into concrete or other surfaces
- Large flat base rated to safely hold up to 44,000 lbs
- Pin Style Stand with 3 adjustment positions

| Heavy-duty stands | S06 (sold as a pair)                                | S020 (single)        | S022 (sold as a pair)                            |
|-------------------|---|----------------------|--|
| Capacity          | 6-ton   | 20-ton               | 22-ton   |
| Max height        | 23-11/16"   | 24"                  | 19-7/8"  |
| Min height        | 15-5/8"   | 15-1/4"              | 13-7/8"  |
| Footprint         | 11-9/16" x 10-3/8" square base;<br>welded foot pads | 15-1/2" square base  | 11" square base, flat for maximum ground contact |
| Adjustment        | Ratcheting; 11 teeth                                | Dual-pin; 4 slots    | Pin-style; 3 slots<br>in 3" increments           |
| Saddle            | V-notch style, 1.2" x 4.2"                          | 6" dia., round steel | 3" x 3-3/4" V-notch                              |

| Under-axle<br>service jack | UA22  | UA27   |
|----------------------------|---|--|
| Capacity                   | 22-ton  | 27.5-ton   |
| Air pressure               | 90 - 145 PSI  | 90 - 175 PSI   |
| Max height                 | 20-2/3" with longest<br>saddle                                | 21-3/8" using longest<br>saddle                                    |
| Min height                 | 8.27"   | 8-1/4"   |
| Handle length              | 47.24" T handle with<br>lowering lever and air-<br>chuck hook | 48-3/4" T handle with<br>lowering lever and air-<br>chuck hook     |
| Footprint                  | 22.63" x 11.73"   | 22" x 12"  |
| Reach                      | 69.87"  | 69.87"   |
| Saddle                     | 3" dia., round with<br>center notch, includes 3<br>lengths    | 3" dia., round with center<br>notch. Includes 2 saddle<br>adapters |
| Frame height               | 8.27"   | 8.27"  |
| Wheels                     | 2 fixed; 7.88"<br>rubberized steel                            | 2 fixed; 7.88"<br>rubberized steel                                 |

#### UA22 22-ton underaxle hydraulic service jack

 Includes 3 saddle attachments for height adjustment; 3/4" saddle; 1-15/16" saddle; 3-7/8" saddle
 Self-retracting ram activated with handle-end controls

## UA27 27.5-ton under axle jack

- 4-position, 48" handle allows easy positioning under vehicles
- Two included saddle attachments increase lifting versatility

NA TOOL

## **MUSCLETOOLS** OTC Transmission and Motorcycle Lift



## 5950D

- Angled Wire Stripping Tool
- Unique design puts stripping dies on the angled tip
- Patented design makes for easier use in hard to reach places
- Works on 12 to 20 AWG wire



## 5019A

## 2,200 Lb. Capacity Low-Lift Transmission Jack

The 8-1/4" low height is perfect for aerodynamic trucks with low ground clearance. Special mounting adapter (No. 540231) fits popular Eaton® Fuller® RoadRanger® transmissions used on nearly all Class 7 and 8 heavyduty trucks. Mounting plate angle is adjusted with the turn of a wrench. Degree of tilt: 20° back, 15° forward, 12° side to side. Swiveling pump handle permits ease of operation in restricted working spaces. Fast-acting pump quickly raises lifting arm.

## 1758

### Fuel tank handler

- Universal adapter plate and adjustability holds tanks up to 40 gallons
- Unique gearing holds load evenly to balance load over jack Heavy-duty foamcovered risers protect tanks and are individually adjustable
- Fits most transmission jacks

## 1797

## Heavy-duty clutch adapter

- Adapter allows high or low-lift transmission jacks to handle heavy-duty clutch assemblies
- Expands use of your transmission jack; accepts optional splined shaft adapters – 545765, 48596, 48625, 440533 and 600011.
- Includes safety strap to securely hold clutch when moving or working







## TJH10

## 1,000-lb Capacity High-Lift Transmission Jack

- Tilting head for easier R&I and positioning of transmissions and other components
- Hydraulic system uses flash-chromed rams to prevent rust, for long shop life
- Limited lifetime warranty
- Meets all the newest ASME PASE safety standards

## 1580

## 1,500 lb. Capacity Easy Roller™

- Provides simple and efficient method of moving a disabled vehicle around a shop environment.
- Fits tread widths up to 12".
- 4 heavy-duty phenolic casters.
- 1,500 lbs. capacity per unit.
- Hydraulic lift mechanism with locking pin.



## Car Dolly (3,600 lbs., capacity pair)

- Innovative patent-pending design clamps directly to pinch welds to prevent slippage during use.
- Independent units eliminate the need to adjust dolly width for different vehicle designs.
- Each unit has an independently adjustable threaded lift saddle with rubber pads to protect the vehicle frame.
- Universal design for use on all vehicle types without additional adapters.
- Provides easy movement of FWD vehicle after removal of drive train.
- The material on the 5" casters is polypropene.
- Each unit has 1,800 lbs. capacity (3,600 lbs., pair) with low height of 9" and high of 14".
- May be used with or without tires on vehicle.





## **OTC Suspension Tools**

## **MUSCLETOOLS**



## Ford Axle Shaft Seal Installers

Correctly installs the seal onto the axle shaft and into the wheel knuckle, preventing front hub vacuum leaks that would cause the 4WD to not engage.

### 6695

Ford Axle Shaft Seal Installer. Works on 1998-2004 Ford F-250, F-350, F-450, and F-550 4X4s having the vacuum-operated front axle.

#### 6697

Ford Axle Shaft Seal Installer. Works on 2005-newer Ford F-250, F-350, 4X4s having the vacuumoperated front axle.

#### 6698

Ford Axle Shaft Seal Installer. Works on 2005-newer Ford F-450, F-550, 4X4s having the vacuumoperated front axle.



6576S both 6576 & 6577 **Dodge Hub Service Set** 

- Removes stubborn hubs, using 2 methods.
- First, the 6576 Hub Pressing Tool is used to press off the hub with the aid of the power steering. The tool locates spacers between the U-joint yoke and axle housing. Unique design makes this a one person operation to remove the hub with the bearing in tact.
- In the event the Hub Pressing Tool does not budge the hub, the 6577 Hub & Bearing Housing Puller is used. This may separate the bearing, but the unique dual pattern design fits both the wheel hub and bearing housing, capable of applying 20 tons of force.

6576 – Hub Pressing Tool, Fits Dodge 3/4 & 1 Ton 4WD 1994-Present applications.

6577 – Hub & Bearing Housing Puller, Fits Dodge 3/4 & 1 Ton 4WD 1994-Present applications. Also fits GM and Ford 4WD Truck hubs.

## 8342 **Hub Resurfacing Kit**

- Fits your power drill to quickly sand rust off studs and mounting surfaces where it is important to have a clean and debris free surface.
- The tool features a 1/4" dia. shank and a stud clearance pilot hole that accepts up to 1/2" studs.
- Sanding pads attach with Half turn thread.
- Includes holder and five sanding discs.
- Run at speeds between 5,000 20,000 rpm or less for best results.



## Hub Grappler<sup>™</sup> Kit

- Jaws designed and sized to properly fit hub applications and is quickly located on the puller bar without the use of fasteners.
- 3/4" custom drive screw coupled with the special equalizer washer provides smooth operation while proprietary heat treating extends its life 5-10 longer than similar designs.
- Six adapters increase application coverage. Includes tie rod/ball joint tool and two Ford axle installers.
- Included Application Guide is the most comprehensive on the market.



## Hydraulic Hub Grappler™ Kit


- An economical way to increase the performance and speed of wheel bearing and hub service.
- Kit includes a through hole 9-ton ram, OTC 2510A air/hydraulic pump, 6 ft. hose with couplers, drive screw and nut.
- Jaws designed and sized to properly fit hub applications and is quickly located on the puller bar without the use of fasteners.
- 3/4" custom drive screw coupled with the special equalizer washer provides smooth operation while proprietary heat treating extends its life 5-10 longer than similar designs.
- Six adapters increase application coverage. Includes tie rod/ball joint tool and two Ford axle installers.
- Included Application Guide is the most comprehensive on the market.



Front Coil Spring Compressor

This compressor fits most late-model rear wheel drive domestic vehicles in which the coil springs are between the upper and lower control arms. The tool features four case-hardened, self-aligning plates to ensure correct load distribution under tension. Includes two 3-3/8" ID plates and two 4" ID plates. Will not work on Mercedes-Benz vehicles.

## 4406 Adjustable Bearing





- Universal and fully adjustable. • Twist head to adjustable from 3/4" to 3.5" (19mm to 89mm).
- Lock bolt holds jaws to preferred diameter.
- Steel striking cap mounted on aluminum handle and head provides a weight under 2 lbs.



#### 7832 GM Torsion Bar Unloader

- Larger design to also cover the newer GM truck applications.
- Application; 2011 & newer HD C/K trucks, 2010 and older GM K3500 series trucks with heavy-duty chassis and a larger torsion bar. 1988 to 2003 GMC and Chevrolet 1/2-, 3/4-, and 1-ton pickups; the S-10 Blazer and S-15 Jimmy, 4WD pickups with 4.3L V-6 engines; and 1991 to 2001 Oldsmobile Bravada.



### 6939 **Broken Bolt Extractor Tool**

- Remove frozen, broken or cut off bolts within steering or suspension bushings.
- Can also be used to remove and install wheel studs and other general pressing needs.



Ford Torsion Bar Adjustment Tool

7816

Before servicing a torsion bar on 1995–2001 Ford Explorer and 1998–2001 Mercury Mountaineer vehicles, you must first contain the bar to avoid possible damage. This tool securely accomplishes that task, allowing you to make adjustments.



#### 7826 Ford Truck Torsion Bar Tool

This tool firmly holds the torsion bar on Ford light-duty trucks while you adjust or service the front suspension. Without it, a torsion bar could unwind and possibly cause damage. The tool fits 1997–2003 Ford F-150 4WD pickups, 1995–2001 Ford Explorer 4WD, 1998–2001 Mercury 15 Mountaineer, and 1998–2001 Ford Ranger.

## MUSCLETOOLS Bosch EV

## **Electric Vehicle Charging Solutions**

NEW

## EV300 Level 2 Charging Station

- Easy to install and use
- Industry standard NEMA 14-50 plug Included
- NEMA 3R-rated enclosure for indoor or outdoor installation (outdoor installation requires in-use cover over receptacle)
- Compact design ideal for areas with limited space (indoor and outdoor)
- Includes tamper resistant mounting bracket
- Easy to manage 16' cable
- 240V, 32A capacity for faster vehicle charging
- Up to 6 times faster than a standard wall outlet
- SAE J1772 charging connector is compatible with all EVs in North America
- 3 year warranty

## EV400 Series Level 2 Charging Station

- 25′ cable is the longest available for more versatility and installation locations
- NEMA 3R-rated enclosure for indoor or outdoor installation (Outdoor installation requires in-use cover over receptacle)
- SAE J1772 charging connector is compatible with all EVs in North America
- Movable, plug-in installation allows charging when you need it, leaving an open outlet when not charging
- Safely charges in all weather conditions rain, snow, sleet, ice and extreme heat or cold
- Bracketless mounting for fast and easy installation
- Clear, bright LEDs indicate charging and power status, stop and reset functions
- Industry leading 4 year warranty

## EV810 Series Level 2 Charging Station

- NEMA4X-rated enclosure is weatherproof for safe charging in any weather or location
- SAE J1772 charging connector is compatible with all EVs in North America
- Flexible mounting. Hardwire from back, top, or side. Can be fitted with included NEMA plug
- Movable, plug-in installation option allows charging when you need it, leaving an open outlet when not charging
- 3 year warranty

## EV3000 DC Fast Charger

- Charge up to 4 times faster than Level 2 AC charging stations
- 30KW DC Charger ideal for fleets, public parking lots and dealerships
- Can charge new vehicles that operate at higher voltages
- SAE J1772 CCS cable included. Compatible with nearly all battery electric vehicles sold in NA
- Wall mountable
- High resolution LCD display
- IP55 rated enclosure for indoor or outdoor installation
- 3 year warranty



Made in

EV860

Made in

the USA

## 23060242\_Muscle Tools\_Q3 2023 edition, Printed in U.S.A.

## All Bosch EV chargers meet either UL/cUL or ETL/cETL safety standards on full units

## EV850 Series Single Bollard Charging Station

- Galvanized steel bollard for parking lot and commercial use - ¼" thick galvanized steel bollard protects against car bumpers, shopping carts and vandalism, protecting your investment
- NEMA4X-rated enclosure is weatherproof for safely charging in any weather or location
- SAE J1772 charging connector is compatible with all EVs in North America
- Hardwire installation and protective bollard creates safe, tamper-proof setup
- Also available as EV860 Dual bollard charging station with two EV810 Series charging stations in a galvanized steel bollard

Made in the USA EV810

22

EV3000

Made in

**NEW** 

EV410

EV300